

CEILING SPEAKERS

IMPROVED



CS510 :
5" 6W 100V Line



CS610 :
6" 6W 100V Line



CS606 :
6" 6W 100V Line

DUAL CONE CEILING SPEAKER WITH ABS ENCLOSURE

Available in 5" and 6" of driver size complete with matching transformer of three tapings ; 1, 3 or 6W. Back enclosure are supplied as integral part of the speakers made from quality ABS plastic. Installation is made easy with its screw mounting mechanism.

Packing information

CS510 : 885 (W) x 363 (H) x 300 (D) mm
: 17 kg
: 20 uts per carton

CS610 : 683 (W) x 473 (H) x 360 (D) mm
: 21.6 kg
: 18 uts per carton

DUAL CONE CEILING SPEAKER WITH METAL ENCLOSURE

Available in 6" dual cone speaker with back metal enclosure, grill and baffle and multi tap matching transformer of 1, 3 and 6W 100V line. This model shall be suitable for installations that demand fire resistant version of dome.

Packing information

CS606 : 540 (W) x 215 (H) x 420 (D) mm
: 12.5 kg
: 10 uts per carton

TECHNICAL SPECIFICATIONS -

	CS510	CS610	CS606
SPEAKER			
Power rating	6W 100V line nominal (max 10W)		6W 100V line nominal
Diameter	5" (125mm)	6" (150mm)	6" (150mm)
Cone type	Dual cone		Dual cone
Impedance	8 Ohm		8 Ohm
Freq response (+/- 5dB)	150 ~ 19 KHz	120 ~ 19 KHz	150 ~ 16 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	93 dB	92 dB	91 dB
Magnet weight	3 oz	5.3 oz	2 oz
TRANSFORMER			
Tapping (100V line)	1 / 3 / 6W 100V line input		1.5 / 3 / 6W 100V line input
Primary impedance (Ohm)	10 K / 3.3 K / 1.6 K Ohm		6.7 K / 3.3 K / 1.6 K Ohm
Secondary impedance	8 Ohm		8 Ohm
MECHANICAL			
Grille / enclosure	White metal / ABS white		White metal
Cutting hole dim (mm)	140	175	165
Overall size (dia x height) mm	177 x 130	230 x 102	200 x 100
Weight	715 g	785 g	950 g
Colour	Off white		Beige white