



CS620 : 6" 20W 100V Line
CS840 : 8" 40W 100V Line

CO-AXIAL CEILING SPEAKER

CS620 and 840 meets the requirement of hi fidelity of sound reproduction in areas such as function halls, restaurants and also for sound reinforcement at hall balconies. They are available in 6" and 8" version of speaker driver with tweeter and 100V line matching transformer.

Packing information

CS620 : 280 (W) x 740 (H) x 545 (D) mm
 : 23 kg
 : 8 uts per carton

CS840 : 335 (W) x 750 (H) x 330 (D) mm
 : 28 kg
 : 8 uts per carton

IP54 RATED



CS343 : 4" 6W 100V Line

WEATHERPROOF CEILING SPEAKER

CS343 is a new addition to the ceiling speaker series, featuring 4" dual cone speaker with built in matching transformer of dual taps of 3 and 6W.

Made of quality ABS enclosure and aluminum grille, it is suitable for high humidity areas, such as bathrooms and salty environment. Though compact in size, it delivers satisfactory sound reproduction with high SPL level, good for listening pleasure as well as paging clarity.

Packing information

CS343 : 610 (W) x 305 (H) x 380 (D) mm
 : 17.4 kg
 : 16 uts per carton

TECHNICAL SPECIFICATIONS -

	CS620	CS840	CS343
SPEAKER			
Power rating	20W 100V	40W 100V	6W 100V line
Diameter	6.5" (160mm)	8" (200mm)	4" (100mm)
Cone type	Co-axial		Dual cone
Impedance	8 Ohm		8 Ohm
Freq response (+/- 5dB)	80 ~ 18 KHz	90 ~ 19 KHz	150 - 18 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	88 dB	90 dB	90 dB
Magnet weight	10 oz	15 oz	-
TRANSFORMER			
Tapping (100V line)	20W 100V line	40W 100V line	3 / 6W 100V line
Primary impedance (Ohm)	500 Ohm	250 Ohm	3.3K / 1.67 K Ohm
Secondary impedance	8 Ohm		8 Ohm
MECHANICAL			
Grille / enclosure	White metal / ABS white		Aluminum / ABS
Cutting hole dim (mm)	205	240	120
Overall size (dia x height) mm	240 x 145	280 x 145	140 x 130
Weight	2.4 kg	2.9 kg	0.9 kg
Colour	Off white		White