

MUSIC & ARRAY SPEAKERS



FS420:
4" 20W 100V Line



FS640:
6" 40W 100V Line

FOREGROUND MUSIC SPEAKER

Available in 4" and 6" of driver size complete with matching transformer selectable power switch and mounting bracket. They are suitable for foreground soft music such as restaurants, shops and general sound reinforcement in meeting room, corridors, etc.

Packing information

FS420 : 350 (W) x 330 (H) x 270 (D) mm
: 10.8 kg
: 4 uts per carton

FS640 : 435 (W) x 420 (H) x 345 (D) mm
: 16 kg
: 4 uts per carton

NOTE : White and Black colour available



FS520:
5" 15W 100V Line



FS625:
6" 25W 100V Line

FOREGROUND MUSIC SPEAKER

These models deliver wider frequency range from bass to treble for satisfying a more demanding audience. Among applications includes bars, restaurants, function halls systems and could easily complement any sound reinforcement systems.

Packing information

FS520 : 415 (W) x 380 (H) x 540 (D) mm
: 18.7 kg
: 8 uts per carton

FS625 : 640 (W) x 415 (H) x 495 (D) mm
: 26 kg
: 8 uts per carton

NOTE : Only Black colour available

TECHNICAL SPECIFICATIONS -

	FS420	FS640	FS520	FS625
SPEAKER				
Power rating	20W	40W	15W	25W
Diameter	4" (100mm)	6" (150mm)	5" (125mm)	6" (150mm)
Cone type	2 way speaker		2 way speaker	
Impedance	8 Ohm		8 Ohm	
Freq response (+/- 5dB)	100 ~ 18 KHz	70 ~ 18 KHz	85 ~ 16 KHz	80 ~ 15 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	89 dB	88 dB	87 dB	89 dB
TRANSFORMER				
Tapping (100V line)	2.5 / 5 / 10 / 20W / 8 Ω	5 / 10 / 20 / 40W / 8 Ω	15W	25W
Primary impedance (Ohm) max / min	4 K / 500 Ohm	2 K / 250 Ohm	667 Ohm	400 Ohm
Secondary impedance	8 Ohm		8 Ohm	
MECHANICAL				
Grille / enclosure	ABS enclosure		ABS enclosure	
Overall size (WxHxD) mm	170 x 215 x 150	215 x 284 x 190	169 x 266 x 160	212 x 328 x 190
Weight	2.2 kg	3.5 kg	2.1 kg	3.0 kg
Colour	White and Black		Black	