

CL700 Series are available in variants of 40W and 80W 100V line with dual power taps. It is built ruggedly with aluminium housing and rust free front aluminum grille. With its IP65 rating, they are suitable for both indoor and outdoor installations.

They are driven by powerful 4" drivers and have been carefully designed and tuned to deliver low frequency and extra emphasis on the mid range, which is important to deliver announcement and EVAC messages.

With its wide range frequency response, it is suitable for applications in hall of prayers, lecture halls, community centers, theme parks and others which demand both music and paging sound quality.



IP65 rated

- **Weatherproof** enclosure with certified IP65 rating
- Ruggedly built with **aluminum** body
- Epoxy coated aluminum grille for **rust free** installation
- **Engineered** for speech and BGM clarity
- **Contemporary design** to match environment
- **Heavy duty** mounting bracket with pan and tilt

CL780
80W 100V

CL740
40W 100V



Universal heavy duty speaker bracket

The heavy duty bracket allows the speaker to be mounted vertically or horizontally with Pan and Tilt adjustment.

Technical Specifications

	CL740	CL780
Power rating	40W 100V	80W 100V
Speaker components	2 x 4" + 1 tweeter	4 x 4" + 2 tweeter
Transformer tapping (100V)	30 / 40W	70 / 80W
Primary impedance (Ohm)	330 / 250	143 / 125
SPL descriptions	88 +/- 3dB	
Freq response @ 1 KHz +/- 3 dB	100 ~ 16 KHz	100 ~ 17 KHz
Dimension (W x H x D)	130 x 310 x 140 mm	130 x 620 x 140 mm
Material	Aluminium body, powder epoxy coated grille	
Weight with bracket	3.5 kg	6.1 kg

Packing Information

CL740 :
Carton size : 370 (L) x 220 (W) x 185 (H) mm
Gross weight : 4.10 kg
1 unit per carton

CL780 :
Carton size : 680 (L) x 230 (W) x 190 (H) mm
Gross weight : 7 kg
1 unit per carton

