

## CD1001

**Integrated CD / DVD / USB / BT / FM Tuner**

CD1001 is rack mounted integrated media player with built in speaker and headphone jack. Suitable for BGM source player in PA installations.



### Features

- Plays various format of DVD / CD audio, MP3 from USB
- FM tuner with 8 station presets
- Bluetooth receiver for playback from external devices
- Local headphone jack
- Monitoring speaker with volume controls

#### Packing information

Carton size : 555 (L) x 295 (W) x 165 (H) mm  
Gross weight : 5.2 kg  
1 unit per carton

## CD1002

**Integrated Dual Ch CD / DVD / USB / BT / FM Tuner**

CD1002 is a compact integrated player with independent dual outputs which can be used for playing two BGM simultaneously. It is suitable for all PA setups such as Matrix system and uninterrupted paging.

**new**



### Features

- Plays various format of DVD / CD audio, MP3 from USB and FM tuner.
- Bluetooth receiver available for receiving external audio transmission
- Independent dual outputs for simultaneous dual BGM playback

#### Packing information

Carton size : 525 (L) x 368 (W) x 120 (H) mm  
Gross weight : 4.0 kg  
1 unit per carton

## MP1020

**Dual Ch. Media Player**

MP1020 is a simple dual channel media player with USB and SD Card MP3 player, FM tuner and aux input. It is suitable for multi source BGM broadcast such as in the Matrix system.



### Features

- Plays various format of MP3 from USB, SD Card and FM tuner.
- Aux inputs with RCA jacks
- Bluetooth receiver available for receiving external audio transmission
- Independent dual outputs for simultaneous dual BGM playback

#### Packing information

Carton size : 555 (L) x 295 (W) x 95 (H) mm  
Gross weight : 2.4 kg  
1 unit per carton

## Technical Specifications

	CD1001	CD1002	MP1020
Operating voltage	220 - 240V AC		24V DC
Power consumption	1.8 W ( 240V AC )	2.5W ( 240V AC )	4.4 W ( 24V DC )
Channels	1	2	
Playback media	CD / DVD / FM tuner / USB, SD card MP3, Bluetooth		FM / USB SD MP3, Bluetooth
USB playback format	MP3, WAV		
Aux input	Nil		RCA Stereo x 2
Output	RCA stereo line out ( 0 dBu , 0.775 V )		
Monitoring	Headphone & Speaker	Nil	
Frequency response ( CD )	20 - 20 kHz		Nil
S/N ratio	> 80 dB		> 60 dB ( USB )
Distortion	< 0.5 % , 1 kHz		
Working temperature	-10 to 55 deg C		
Humidity	85 %		
Dimensions ( WxHxD ) mm	482 x 88 x 180	482 x 44 x 365	482 x 44 x 180
Net weight ( kg )	4.25	2.70	1.80