



**CS610 / CS610B**

6" 6W 100V / 6" 10W 100V

**CS610 FR - Fire Retardant Enclosure**



**CS510**

5" 6W 100V

**CS510 FR - Fire Retardant Enclosure**



**CS210**

2" 6W 100V

**CS210 / 510 / 610** are general purpose speakers suitable for paging and BGM applications which not only deliver the required audio quality but also fits into every installation with its contemporary outlooks. It is designed with slim edges for cozy appearance and the clamping mechanism that provide ease of installation works.

- **High quality** ABS enclosure
- **Spring clip** for ease of installations
- **Slim edge** design with low side profile
- Option for installation **without enclosure**
- **Fire retardant (FR)** grade materials available as an option



spring clip installation

**Technical Specifications**

	<b>CS210</b>	<b>CS510</b>	<b>CS610</b>	<b>CS610B</b>
Power rating		6W 100V line		10W 100V line
Diameter	2" (51 mm)	5" (125 mm)	6" (150 mm)	
Cone type	Single cone	Dual cone		
Impedance (Ohm)	8			
Freq response @ 1KHz +/- 3dB	160 ~ 15 KHz	150 ~ 19 KHz	120 ~ 19 KHz	
SPL @ 1W / m (+/-3dB) 1 KHz	90 dB	92 dB		
Dispersion angle (1KHz +/-3 dB)	120	160	165	165
Tapping (100V line)		1.5 / 3 / 6W	1 / 3 / 6 / 10W	
Primary impedance (Ohm)		6.7k / 3.3k / 1.67k	10k / 3.3k / 1.67k / 1k	
Secondary impedance (Ohm)	8			
Grille / enclosure	Aluminium grille / ABS enclosure		Metal grille / ABS enclosure	
Cutting hole diameter	85 mm	145 mm	185 mm	
Overall size (diameter x height)	110 x 110 mm	165 x 110 mm	205 x 110 mm	
Weight	500 g	780 g	840 g	850 g
Colour	White			

**Packing Information**

**CS210 :**  
 Carton size : 570 (L) x 230 (W) x 290 (H) mm  
 Gross weight : 11.30 kg  
 20 units per carton

**CS510 :**  
 Carton size : 690 (L) x 350 (W) x 400 (H) mm  
 Gross weight : 19.60 kg  
 24 units per carton

**CS610 / 610B :**  
 Carton size : 660 (L) x 440 (W) x 430 (H) mm  
 Gross weight : 19.50 / 19.75 kg  
 20 units per carton



[www.ampereselectronics.com](http://www.ampereselectronics.com)