

4" / 5" 100V LINE SURFACE MOUNT SPEAKER

BS508
BS506
BS410
DV410



BS508 - 5" 10W 100V

NEW

BS508 : SURFACE MOUNT / BOX SPEAKER

BS508 is a surface mount / box speaker with 5" driver with power tapping at 1, 3, 6 and 10W. It is built with quality ABS material for ruggedness and solid sound reproduction.

It has lower profile enclosure as compared with other conventional box speakers, thereby able to blend to most installation places.

BS508 has been tuned to deliver optimum sound for BGM, Paging and EVAC purposes with emphasis on human voice.



BS506 - 5" 6W 100V

BS506 : SURFACE MOUNT SPEAKER

Need not worry about rust with BS506 which is built from high quality ABS material. It delivers satisfactory sound reproduction with its 5" driver.

Packing information

BS506 : 550 (L) x 400 (W) x 180 (H) mm
: 10.00 kg
: 12 uts per carton



BS410 - 4" 10W 100V

BS410 : SURFACE MOUNT SPEAKER

It is constructed with high quality ABS plastic with 4" dual cone speaker driver and multi tapping matching transformer of 1 / 3 / 6 and 10W 100 V line. Suitable for wall and ceiling installation with optional tilt mounting bracket. Available in white colour.

Packing information

BS410 : 550 (L) x 420 (W) x 220 (H) mm
: 9.85 kg
: 12 uts per carton



DV410 - 4" 6W 100V

DV410 : SURFACE MOUNT SPEAKER

A classic yet favourite model which is suitable for installations in small enclosed areas such as staircase, office, etc. Available in white colour with multi tap matching transformer of 1 / 3 / and 6W 100V line, fit for vertical or horizontal installations.

Packing information

DV410 : 460 (L) x 420 (W) x 410 (H) mm
: 16.70 kg
: 20 uts per carton

Technical Specifications

	BS508	BS506	BS410	DV410
SPEAKER				
Power rating	10W 100V	6W 100V	10W 100V	6W 100V
Diameter	5"		4"	
Cone type	Dual cone			
Impedance (Ohm)	8			
Freq response @1KHz +/- 3dB	120 - 18 KHz	100 ~ 15 KHz	100 ~ 16 KHz	100 ~ 18 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	94 dB	93 dB	92 dB	90 dB
TRANSFORMER				
Tapping (100V line)	1 / 3 / 6 / 10W	1 / 3 / 6W	1 / 3 / 6 / 10W	1 / 3 / 6W
Primary impedance (Ohm)	10 K / 3.3 K / 1.6 K / 1K	10K / 3.3K / 1.6K	10 K / 3.3 K / 1.6 K / 1K	10K / 3.3K / 1.6K
Secondary impedance (Ohm)	8			
PHYSICAL				
Grille / enclosure	ABS plastic		ABS with metal grille	
Overall size (W x H x D) mm	220 x 130 x 68	172 x 195 x 105	185 x 215 x 90	195 x 215 x 105
Weight	720 g	780 g	760 g	740 g
Colour	White			