CS606 CS343 CS515 CS516

Dual Cone Ceiling Speakers



CS606

6" 6W 100V Line



CS343

4" 6W 100V Line

IP65

CS606 is a robust 6" speaker combines decent sound with essential safety features, including a epoxy coated metal enclosure and a corrosion-resistant aluminum grille. With various power taps (1.5W to 6W) and a quick-install spring clamp system, it is the perfect solution for effortless, professional sound.

CS343 is an IP65-rated weatherproof speaker designed for a more demanding environment such as high-humidity cleanrooms, spas etc. its ABS enclosure and rust-resistant aluminum grille provide uncompromising durability without sacrificing audio clarity.



CS515 (W/B)

5" 6W 100V Line

FR ABS ENCLOSURE AVAILABLE



CS516 (W/B)

5" 6W 100V Line



Back enclosure is optional and sold separately

CS515 is a 5" full-ABS ceiling speaker with a unique honeycomb grille, suitable for BGM and paging applications. Its ABS enclosure and baffle make it ideal for humid areas where rust or chemical erosions are often encountered. Ideal for sea side installations or high humidity hill resorts.

CS516 is a full-ABS surface-mount ceiling speaker for solid slab ceilings, with unique honeycomb grille, and multiple power taps of 1.5W / 3W / 6W 100V line. It is suitable where recessed speakers can't be used. Optional back cover is available to provide total cover.

Model Variants

CS515	Available in white (W) & black (B)
CS515FR	Fire-retardant (FR) ABS enclosure

Model Variants

CS516	Available in white (CS516W) and black (CS516B)
CS516B(B)	With matching transformer 1W / 3W / 6W / 10W

Technical Specifications

	CS606	CS515	CS516	CS343
Power rating	6W 100V line nominal (Max 10W)			
Diameter	6" (150 mm)	5" (125 mm)		4" (100 mm)
Cone type	Dual cone			
Driver impedance (Ohm)	8 Ohm			
Freq. response @ 1 kHz ± 3 dB	150 - 16 kHz	150 - 17 kHz		150 - 18 kHz
SPL @ 1W/m (1 kHz ± 3 dB)	91 dB	92 dB		90 dB
Power taps (100V line)	1.5W / 3W / 6W			3W / 6W
Primary impedance (Ohm)	6.7k / 3.3k / 1.67k Ohm			3.3k / 1.67k Ohm
Secondary impedance (Ohm)	8 Ohm			
Grille & enclosure material	Aluminium grille & metal enclosure	ABS grille & enclosure		Aluminium grille & ABS enclosure
Cutting hole diameter (D)	165 mm	145 mm	N/A	120 mm
Dimensions (diameter x height)	200 x 70 mm	175 x 95 mm	222 x 65 mm	140 x 130 mm
Net weight	780 g	620 g	660 g	850 g
Colour	White	White / Black		White

Packing Information

	CS606	CS515 / CS515FR	CS516	CS343
Carton size	465 (L) x 430 (W) x 435 (H) mm	705 (L) x 400 (W) x 190 (H) mm	565 (L) x 430 (W) x 240 (H) mm	370 (L) x 370 (W) x 600 (H) mm
Gross weight	21.0 kg	11.30 kg (**CS515**)	12.40 kg	18.80 kg
Qty/carton	20 units per carton	16 units per carton	16 units per carton	16 units per carton