

CL900 SERIES

Slim Column Speakers

SPEAKERS

Built ruggedly with aluminium die extrusion housing and is available 5 power ratings of 10, 20, 40, 60 and 80W 100V line, each with dual power taps. They are suitable for classrooms, hyper markets, mosques, ballroom, factories, passenger terminals, exhibition areas etc.

- **Slim design** to match environment or to be hidden from view
- **Epoxy** coated grille
- **Engineered** for speech and BGM clarity
- **Multi-way mounting bracket** for CL902, CL904, CL908 and heavy duty metal bracket for CL912 and CL916.



Technical Specifications

	CL902	CL904	CL908	CL912	CL916
Power rating	10W 100V	20W 100V	40W 100V	60W 100V	80W 100V
Speaker components	2 X 2"	4 X 2"	8 X 2"	12 X 2"	16 X 2"
Transformer tapping (100V)	6 / 10W	10 / 20W	30 / 40W	50 / 60W	70 / 80W
Primary impedance (Ohm)	1.6k / 1k	1k / 500	330 / 250	200 / 166	143 / 125
SPL descriptions	87 +/- 3 dB		88 +/- 3 dB	89 +/- 3 dB	94 +/- 3 dB
Freq response @ 1kHz +/-3 dB	200 ~ 16 KHz	200 ~ 17 KHz	240 ~ 16 KHz	220 ~ 17 KHz	220 ~ 18 KHz
Dimensions (W x H x D)	79 x 190 x 89 mm	79 x 350 x 89 mm	79 x 567 x 89 mm	79 x 782 x 89 mm	79 x 1128 x 89 mm
Material	Aluminium body ; powder epoxy metal grille				
Weight with bracket	1.10 kg	1.50 kg	2.50 kg	3.20 kg	5.80 kg

Packing Information

CL902 :

Carton size : 255 (L) x 235 (W) x 170 (H) mm
Gross weight : 2.70 kg
2 units per carton

CL912 :

Carton size : 830 (L) x 245 (W) x 170 (H) mm
Gross weight : 7.80 kg
2 units per carton

CL904 :

Carton size : 400 (L) x 235 (W) x 155 (H) mm
Gross weight : 3.90 kg
2 units per carton

CL916 :

Carton size : 1160 (L) x 240 (W) x 195 (H) mm
Gross weight : 13.00 kg
2 units per carton

CL908 :

Carton size : 605 (L) x 245 (W) x 175 (H) mm
Gross weight : 6.20 kg
2 units per carton

