

- CS343** 4" 6W 100V Weatherproof
- CS515** 5" 6W 100V ABS Grille
- CS606** 6" 6W 100V Metal Enclosure
- CS516** 6" 10W 100V ABS Surface Mount



CS515 5" 6W 100V Line
CS515 FR With fire retardant back enclosure

CS515 is a general purpose ceiling speaker with ABS honeycomb grille and back enclosure. It is suitable for BGM and Paging applications. With ABS enclosure and baffle, issues on rust / chemical erosions is avoided. Fire retardant enclosures are available as an option (CS515FR)

Packing information

Carton : 705 (L) x 400 (W) x 190 (H) mm
 Gross weight : 11.30 kg
 16 unit per carton



CS606 6" 6W 100V Line

Available in 6" dual cone speaker with back metal enclosure, grille and baffle and multi tap matching transformer of 1.5, 3 and 6W 100V line. This model shall be suitable for installations that demand fire resistant version of dome.

Packing information

Carton : 590 (L) x 400 (W) x 310 (H) mm
 Gross weight : 16.80 kg
 20 units per carton



CS343 4" 6W 100V Line

IP65

CS343 is driven by a 4" dual cone speaker with built in matching transformer of dual taps for 3 and 6W 100V line. It is made of quality ABS enclosure and aluminum grille and is suitable for high humidity areas, such as bathrooms and salty environment. With its IP65 rating, it is also suitable for clean area installations. Though compact in size, it delivers satisfactory sound reproduction with high SPL level, good for listening pleasure as well as paging clarity.

Packing information

Carton : 370 (L) x 370 (W) x 600 (H) mm
 Gross weight 16.30 kg
 16 uts per carton



CS516 - 5" 6W 100V

CS516 is a general purpose surface mount speaker suitable for direct installations at ceiling slabs in which recessed type of speakers are not suitable.

Packing information

Carton : 550 (L) x 420 (W) x 220 (H) mm
 Gross weight : 11.40 kg
 16 units per carton

Technical Specifications

	CS606	CS515	CS516	CS343
SPEAKER				
Power rating	6W 100V line nominal (max 10W)			
Diameter	6" (150 mm)	5" (125 mm)		4" (100 mm)
Cone type	Dual cone			
Impedance (Ohm)	8			
Freq response @ 1kHz +/-3dB	150 ~ 16 kHz	150 ~ 17 kHz		150 - 18 kHz
SPL @ 1W / m (+/- 3dB) 1 kHz	91 dB	92 dB		90 dB
TRANSFORMER				
Tapping (100V line)		1.5 / 3 / 6W		3 / 6W
Primary impedance (Ohm)		6.7k / 3.3k / 1.67k		3.3k / 1.67 k
Secondary impedance (Ohm)	8			
PHYSICAL				
Grille / enclosure	Aluminum / mild steel	ABS Plastic		Aluminum / ABS
Cutting hole dim	165 mm	145 mm	-	120 mm
Overall size (dia x height)	200 x 70 mm	175 x 95 mm	222 x 65 mm	140 x 130 mm
Weight	780 g	620 g	660 g	850 g
Colour	White		White / Black	White

