



Features

- ▶ 8 channel with 6A per channel; total load of 15A with surge protection
- ▶ Cascade 2 units to form 16 channel setup
- ▶ ON / OFF sequential switching
- ▶ Remote switching port via external noiseless contact
- ▶ AC output via IEC connectors with channel isolation via DIP switch
- ▶ Ch. 8 with delay Off option for 2 min ; suitable for video projector connection
- ▶ Lock mode to avoid incidental switching

Technical Specifications

Operating voltage	220 - 240V AC
Power consumption	50 mW (without load)
Output voltage	230 / 240V AC
Max load / channel	6A
Max total load	15A
Output connection	IEC female socket
Max cascade	2 uts : total 16 channels
Surge protection	L-N, L-E, N-E.
Clamping voltage	870V AC
Turn on sequence	Step 1 to 8 incremental
Turn off sequence	Step 8 to 1 decremental
Step timing	2 seconds
Delay off option	Channel 8 via DIP switch
Delay off timer	2 minutes
Switch lock	Via front switch
Indicators	AC mains, Ch. on, Lock
Dimensions (W x H x D)	482 x 44 x 180 mm
Weight	2.80 kg excl. accessories

SQ9815 is suitable for applications in PA, sound and AV system in which it manages the powering sequence of every equipment in orderly manner. It works to provide a some degree of protection to the lifespan of the equipment as random powering may cause irreversible damage.

It has internal surge protection to kill harmful incoming power spikes. An important tool that works to safely powering up your equipment with a touch of a button.

Rear View:



Packing information
 Qty per carton : 1 unit
 L x W x H : 555 x 295 x 95 mm
 Weight : 3.55 kg

Regulated 24V DC Power Supply | PS9400



Technical Specifications

Operating voltage	220 - 240V AC
Output voltage	24V +/- 1%
Rating	4A nominal ; max 5.5A
No load consumption	50 mW
Efficiency	83%
Indicators	AC mains, battery input, DC output
Protections	Built in surge protection Short circuit Overload (105% ~ 150%) Over voltage (115% ~ 135%)
Output DC protection	Fuse
Terminals	Batt input and load ; barrier connector
Dimensions (W x H x D)	482 x 44 x 180 mm
Weight	2.35 kg

PS9400 is a rack mounted 24V DC regulated power pack designed uniquely for PA installations. It comes with built in changeover relay which shall be connected to back up 24V DC to allow continuous and uninterrupted supply to the whole installation whenever the mains failed.

Features

- ▶ 24V DC 4A output highly regulated PSU
- ▶ Output Fuse protection
- ▶ Built in various protection
- ▶ Back up battery overriding relay

Rear View:



Packing information
 Qty per carton : 1 unit
 L x W x H : 555 x 295 x 95 mm
 Weight : 3.00 kg